



Parameters of DZ25-2 model Concrete Laser Screed

Product type	Name	concrete laser screed	Unit
	Type	DZ25-2	
Engine	Mode	SAWAFUJI Honda SH3900EX	
	Type	Electric 220V-50Hz	
	Power	3.3	HP
	Lubrication oil level	0.6-0.8	L
	Fuel tank volume	18	L
	Working mode of screed head	Rocking type	
Leveling system	Screed width	2500	mm
	Paving mode	Vibrating plate spreading	
	Paving thickness	50-200	mm
	Screw conveyor power	-	
	Control mode of vibrating system	Vibration motor	
	Excitation force	2000	N
	Vibration frequency	50	Hz
Laser system	Control mode of laser system	Microcomputer laser scanning	
	Control effect of laser system	Flat surface、 Slope、 Double slope (three-dimensional)	
Driving system	Drive type	Reducer+Motor	
	Wheel	Solid puncture proof tyre/Special use wide tire	
	Speed	0-40	m/min
Operation modes	Seat position		
	Forward,back away	Manual control	
Cleaning system	Turning	Manual control	
	Power	Alternator	
	Theoretical flow	20	L/min
	Rated pressure	7	Mpa
Size and weight	Outline dimension	3220*2780*1180	mm
	Net weight	430	Kg

CONTACT US

27/232 Moo.5, Pantainorasingh, MuangSamutsakhon District,

Samutsakhon 74000 Thailand

086-336-1736 , 063-425-9988

vanse.asia@gmail.com